

A survey of unhandledRejection and rejectionHandled handlers

This article was originally published at

<https://gist.github.com/joepie91/06cca7058a34398f168b08223b642162>.

Bluebird (<http://bluebirdjs.com/docs/api/error-management-configuration.html#global-rejection-events>)

- `process.on//unhandledRejection` : **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled` : **(Node.js)** Cancel unhandled rejection, it was handled anyway.
- `self.addEventListener//unhandledrejection` : **(WebWorkers)** Potentially unhandled rejection.
- `self.addEventListener//rejectionhandled` : **(WebWorkers)** Cancel unhandled rejection, it was handled anyway.
- `window.addEventListener//unhandledrejection` : **(Modern browsers, IE >= 9)** Potentially unhandled rejection.
- `window.addEventListener//rejectionhandled` : **(Modern browsers, IE >= 9)** Cancel unhandled rejection, it was handled anyway.
- `window.onunhandledrejection` : **(IE >= 6)** Potentially unhandled rejection.
- `window.onrejectionhandled` : **(IE >= 6)** Cancel unhandled rejection, it was handled anyway.

WhenJS (<https://github.com/cujojs/when/blob/3.7.0/docs/debug-api.md>)

- `process.on//unhandledRejection` : **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled` : **(Node.js)** Cancel unhandled rejection, it was handled anyway.
- `window.addEventListener//unhandledRejection` : **(Modern browsers, IE >= 9)** Potentially unhandled rejection.
- `window.addEventListener//rejectionHandled` : **(Modern browsers, IE >= 9)** Cancel unhandled rejection, it was handled anyway.

Spec (<https://gist.github.com/benjaminr/0237932cee84712951a2>)

- `process.on//unhandledRejection` : **(Node.js)** Potentially unhandled rejection.

- `process.on//rejectionHandled` : **(Node.js)** Cancel unhandled rejection, it was handled anyway.

Spec (WHATWG: <https://html.spec.whatwg.org/multipage/webappapis.html#unhandled-promise-rejections>)

- `window.addEventListener//unhandledrejection` : **(Browsers)** Potentially unhandled rejection.
- `window.addEventListener//rejectionhandled` : **(Browsers)** Cancel unhandled rejection, it was handled anyway.
- `window.onunhandledrejection` : **(Browsers)** Potentially unhandled rejection.
- `window.onrejectionhandled` : **(Browsers)** Cancel unhandled rejection, it was handled anyway.

ES6 Promises in Node.js (https://nodejs.org/api/process.html#process_event_rejectionhandled onwards)

- `process.on//unhandledRejection` : Potentially unhandled rejection.
- `process.on//rejectionHandled` : Cancel unhandled rejection, it was handled anyway.

Yaku (<https://github.com/ysmood/yaku#unhandled-rejection>)

- `process.on//unhandledRejection` : **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled` : **(Node.js)** Cancel unhandled rejection, it was handled anyway.
- `window.onunhandledrejection` : **(Browsers)** Potentially unhandled rejection.
- `window.onrejectionhandled` : **(Browsers)** Cancel unhandled rejection, it was handled anyway.

Revision #1

Created 11 December 2024 12:27:50 by joepie91

Updated 11 December 2024 18:44:19 by joepie91