

A survey of unhandledRejection and rejectionHandled handlers

This article was originally published at

<https://gist.github.com/joepie91/06cca7058a34398f168b08223b642162>.

Bluebird (<http://bluebirdjs.com/docs/api/error-management-configuration.html#global-rejection-events>)

- `process.on//unhandledRejection`: **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled`: **(Node.js)** Cancel unhandled rejection, it was handled anyway.
- `self.addEventListener//unhandledrejection`: **(WebWorkers)** Potentially unhandled rejection.
- `self.addEventListener//rejectionhandled`: **(WebWorkers)** Cancel unhandled rejection, it was handled anyway.
- `window.addEventListener//unhandledrejection`: **(Modern browsers, IE >= 9)** Potentially unhandled rejection.
- `window.addEventListener//rejectionhandled`: **(Modern browsers, IE >= 9)** Cancel unhandled rejection, it was handled anyway.
- `window.onunhandledrejection`: **(IE >= 6)** Potentially unhandled rejection.
- `window.onrejectionhandled`: **(IE >= 6)** Cancel unhandled rejection, it was handled anyway.

WhenJS (<https://github.com/cujojs/when/blob/3.7.0/docs/debug-api.md>)

- `process.on//unhandledRejection`: **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled`: **(Node.js)** Cancel unhandled rejection, it was handled anyway.
- `window.addEventListener//unhandledRejection`: **(Modern browsers, IE >= 9)** Potentially unhandled rejection.
- `window.addEventListener//rejectionHandled`: **(Modern browsers, IE >= 9)** Cancel unhandled rejection, it was handled anyway.

Spec (<https://gist.github.com/benjaminr/0237932cee84712951a2>)

- `process.on//unhandledRejection`: **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled`: **(Node.js)** Cancel unhandled rejection, it was handled anyway.

Spec (WHATWG: <https://html.spec.whatwg.org/multipage/webappapis.html#unhandled-promise-rejections>)

- `window.addEventListener//unhandledrejection`: **(Browsers)** Potentially unhandled rejection.
- `window.addEventListener//rejectionhandled`: **(Browsers)** Cancel unhandled rejection, it was handled anyway.
- `window.onunhandledrejection`: **(Browsers)** Potentially unhandled rejection.
- `window.onrejectionhandled`: **(Browsers)** Cancel unhandled rejection, it was handled anyway.

ES6 Promises in Node.js (https://nodejs.org/api/process.html#process_event_rejectionhandled onwards)

- `process.on//unhandledRejection`: Potentially unhandled rejection.
- `process.on//rejectionHandled`: Cancel unhandled rejection, it was handled anyway.

Yaku (<https://github.com/ysmood/yaku#unhandled-rejection>)

- `process.on//unhandledRejection`: **(Node.js)** Potentially unhandled rejection.
- `process.on//rejectionHandled`: **(Node.js)** Cancel unhandled rejection, it was handled anyway.
- `window.onunhandledrejection`: **(Browsers)** Potentially unhandled rejection.
- `window.onrejectionhandled`: **(Browsers)** Cancel unhandled rejection, it was handled anyway.

Revision #1

Created 2024-12-11 12:27:50 UTC by joepie91

Updated 2024-12-11 18:44:19 UTC by joepie91